

Polyurethane lining

J 24 - J 604

SULZER

General


Sulzer offers PU Lining, a solution where the diffusers and wear rings are coated with polyurethane.

Impellers are designed with a full upper shroud, which improves the wear resistance of the impeller and eliminates the need of polyurethane on the oil casing cover.

Application

Polyurethane coated wear parts are mainly used in extremely abrasive applications such as mining.

Polyurethane coated diffusers and wear rings are available as an option on J 24 - J 44, JC 24 - JC 44, J 54 - J 84, JC 54 - JC 84, J 205, J 405 and J 604.



PU Lining available

Pump model	P/N	Description
J/JC 24 ND, HD	00830248*	Diffuser + 4 bushings
J/JC 44 ND, HD	00830248*	Diffuser + 8 bushings (50 Hz) Diffuser + 4 bushings (60 Hz)
J/JC 54 ND, HD	00830249	Diffuser
J/JC 84 ND, HD 60 Hz	00830249	Diffuser
J 205 ND	00831639	Wear ring
J 205 HD	00830247	Wear ring
J 405 ND	00831640	Wear ring
J 405 HD	00831270	Wear ring
J 604 ND	00831642	Wear ring
J 604 HD	00831641	Wear ring

* complete kit for both J 24-J 44 and JC 24-JC 44